

EXPLOSION PROOF,

VERSATILE AND ENERGY EFFICIENT

This Class I Division 1, superior designed, lightweight, compact, LED area light is made for the most demanding environments and provides unmatched lighting performance with up to 162 lumens per watt.

It is ideally suited for low mounting heights in offshore, gas, mining, particulate, chemical and other volatile environments.

RED SKY
SERIOUSLY SAFE LIGHTS**









RATINGS & CERTIFICATIONS

- > Class I Division 1
- > Class I Division 2
- > Class II Division 1
- > Class III









SPECIFICATIONS

VOLTAGE/FREQUENCY 120-277V AC 347-480V AC 50/60HZ POWER 21W 40W 50W 60W LUMEN OUTPUT 4220/6500/7180/8515 AVAILABLE BEAM ANGLES T2/T3/T5 OPERATING TEMPERATURE 21W / 40W / 50W : -40°F ~ +149°F (-40°C ~ +65°C) 60W : -40°F ~ +147°F (-40°C ~ +64°C) DIMENSIONS 9.7×8.3×5.1in (244×211×130 mm) WEIGHT 13.9lbs/6.3kg CONSTRUCTION Marine Grade Cast Aluminum LENS MATERIAL Tempered glass(Clear/Frosted) HARDWARE Stainless Steel 316 FINISH Thermoset Powdercoat CONNECTION (1) 3/4" NPT w/ 3' 18/3 leads L70 130,000 Hours@149°F WARRANTY LEDs: 10 years Driver: 7 years		
LUMEN OUTPUT 4220/6500/7180/8515 AVAILABLE BEAM ANGLES T2/T3/T5 OPERATING TEMPERATURE 21W / 40W / 50W : -40°F ~ +149°F (-40°C ~ +65°C) 60W : -40°F ~ +147°F (-40°C ~ +64°C) DIMENSIONS 9.7×8.3×5.1in (244×211×130 mm) WEIGHT 13.9lbs/6.3kg CONSTRUCTION Marine Grade Cast Aluminum LENS MATERIAL Tempered glass(Clear/Frosted) HARDWARE Stainless Steel 316 FINISH Thermoset Powdercoat CONNECTION (1) 3/4° NPT w/ 3' 18/3 leads L70 130,000 Hours@149°F	VOLTAGE/FREQUENCY	120-277V AC 347-480V AC 50/60HZ
AVAILABLE BEAM ANGLES OPERATING TEMPERATURE DIMENSIONS 0.7×8.3×5.1in (244×211×130 mm) WEIGHT CONSTRUCTION LENS MATERIAL HARDWARE FINISH Tompered glass (Clear/Frosted) FINISH CONNECTION (1) 3/4" NPT w/ 3' 18/3 leads L70 130,000 Hours@149°F	POWER	21W 40W 50W 60W
OPERATING TEMPERATURE 21W / 40W / 50W : -40°F ~ +149°F (-40°C ~ +65°C) 60W : -40°F ~ +147°F (-40°C ~ +64°C) DIMENSIONS 9.7×8.3×5.1in (244×211×130 mm) WEIGHT 13.9lbs/6.3kg CONSTRUCTION Marine Grade Cast Aluminum LENS MATERIAL Tempered glass(Clear/Frosted) HARDWARE Stainless Steel 316 FINISH Thermoset Powdercoat CONNECTION (1) 3/4° NPT w/ 3' 18/3 leads L70 130,000 Hours@149°F	LUMEN OUTPUT	4220/6500/7180/8515
OPERATING TEMPERATURE 60W: -40°F ~ +147°F (-40°C ~ +64°C) DIMENSIONS 9.7×8.3×5.1in (244×211×130 mm) WEIGHT 13.9lbs/6.3kg CONSTRUCTION Marine Grade Cast Aluminum LENS MATERIAL Tempered glass(Clear/Frosted) HARDWARE Stainless Steel 316 FINISH Thermoset Powdercoat CONNECTION (1) 3/4° NPT w/ 3' 18/3 leads L70 130,000 Hours@149°F	AVAILABLE BEAM ANGLES	T2/T3/T5
WEIGHT 13.9lbs/6.3kg CONSTRUCTION Marine Grade Cast Aluminum LENS MATERIAL Tempered glass(Clear/Frosted) HARDWARE Stainless Steel 316 FINISH Thermoset Powdercoat CONNECTION (1) 3/4" NPT w/ 3' 18/3 leads L70 130,000 Hours@149"F	OPERATING TEMPERATURE	
CONSTRUCTION Marine Grade Cast Aluminum LENS MATERIAL Tempered glass(Clear/Frosted) HARDWARE Stainless Steel 316 FINISH Thermoset Powdercoat CONNECTION (1) 3/4" NPT w/ 3' 18/3 leads L70 130,000 Hours@149"F	DIMENSIONS	9.7×8.3×5.1in (244×211×130 mm)
LENS MATERIAL Tempered glass(Clear/Frosted) HARDWARE Stainless Steel 316 FINISH Thermoset Powdercoat CONNECTION (1) 3/4" NPT w/ 3' 18/3 leads L70 130,000 Hours@149°F	WEIGHT	13.9lbs/6.3kg
Tempered glass (Clear/Frosted) HARDWARE Stainless Steel 316 FINISH Thermoset Powdercoat	CONSTRUCTION	Marine Grade Cast Aluminum
FINISH Thermoset Powdercoat CONNECTION (1) 3/4" NPT w/ 3' 18/3 leads L70 130,000 Hours@149°F	LENS MATERIAL	Tempered glass(Clear/Frosted)
CONNECTION (1) 3/4" NPT w/ 3' 18/3 leads L70 130,000 Hours@149°F	HARDWARE	Stainless Steel 316
L70 130,000 Hours@149°F	FINISH	Thermoset Powdercoat
	CONNECTION	(1) 3/4" NPT w/ 3' 18/3 leads
WARRANTY LEDs: 10 years Driver: 7 years	L70	130,000 Hours@149°F
	WARRANTY	LEDs: 10 years Driver: 7 years

CONTACT OUR TEAM TODAY

1 (833) 4 REDSKY contact@redskylighting.com www.redskylighting.com