

LINEAR LITE SERIES

ECONOMICAL

TRI-PROOF FOR ROUGH SERVICE

The Linear Lite Series is designed for harsh marine and industrial environments. It is available with a tempered glass, PC, or PMMA lens.

Durable construction with an IP66 rating and IK10 shock rating, the Linear Lite can handle water, dust, humidity, corrosion, and other harsh environments with extreme ease.



RED SKY
SERIOUSLY SAFE LIGHTS™



RATINGS & CERTIFICATIONS



SPECIFICATIONS

VOLTAGE/FREQUENCY	120-277V AC 50/60HZ
POWER	20W, 60W
LUMEN OUTPUT	2400/7200
AVAILABLE BEAM ANGLES	120°,60°
OPERATING TEMPERATURE	-4°F ~ +104°F (-20°C ~ +40°C)
DIMENSIONS	20W: 25.4×4.4×3.5in (645×112×89 mm) 60W: 59.1×4.4×3.5in (1500×112×89 mm)
WEIGHT	20W: 2.65lbs/1.2kgs 60W: 5.95lbs/2.7kgs
CONSTRUCTION	Galvanized Steel Housing, Die-cast aluminum End-caps
LENS MATERIAL	Tempered glass, Polycarbonate, PMMA
HARDWARE	Marine Grade Stainless Steel
FINISH	Thermoset Powdercoat
CONNECTION	1.2M/3.9' Cable
L70	70,000 Hours
WARRANTY	5 Years

CONTACT OUR TEAM TODAY

1 (833) 4 REDSKY

contact@redskylighting.com

www.redskylighting.com