

RED SKY

SERIOUSLY SAFE LIGHTS™













RATINGS & CERTIFICATIONS

- > Class I Division 2
- > Class II Division 2
- > Class II Division 1
- > Class III







SPECIFICATIONS

VOLTAGE/FREQUENCY	100-277V AC 347-480V AC 50/60Hz
POWER	80W, 120W, 150W, 200W
LUMEN OUTPUT	12000/18000/22500/30000
AVAILABLE BEAM ANGLES	T1/T3/T5
OPERATING TEMPERATURE	80W/120W: -40°F ~ +149°F (-40°C ~ +65°C) 150W: -40°F ~ +140°F (-40°C ~ +60°C) 200W: -40°F ~ +131°F (-40°C ~ +55°C)
DIMENSIONS	Ф10.6×9.1in (Ф270×230mm)
WEIGHT	21.6lbs/9.8kg
CONSTRUCTION	Die Cast Aluminum
LENS MATERIAL	Tempered Glass or Polycarbonate
HARDWARE	Stainless Steel 316
FINISH	Thermoset Powdercoat
CONNECTION	(6) 3/4" NPT
L70	145,000 Hours@131°F
WARRANTY	LEDs: 10 years Driver: 5 years

CONTACT OUR TEAM TODAY

1 (833) 4 REDSKY contact@redskylighting.com www.redskylighting.com