

TUFF TUBE SERIES

IP69K AND IK10 SHOCK RATED

The Tuff-Tube is perfect for harsh conditions in polluted environments where a high level of quality lighting is needed. Rated IP69K with an IK10 shock rating, the Tuff-Tube handles water, dust, humidity, corrosion, vibration, and sudden impact with ease.

Constructed of a high-quality PC/PE tubular housing and stainless steel caps, this fixture can be used indoors or outdoors and installs easily with little maintenance over the lifetime of the fixture.

The Tuff-Tube is perfect for agricultural and livestock applications, food processing plants, refrigeration specification, and car washes.

RED SKY
SERIOUSLY SAFE LIGHTS™



RATINGS & CERTIFICATIONS

- > UL
- > IK10
- > IP69K
- > NSF



SPECIFICATIONS

VOLTAGE/FREQUENCY	120-277V AC 50/60Hz
POWER	20W, 36W, 45W
LUMEN OUTPUT	2700/4860/6075
AVAILABLE BEAM ANGLES	120°
DIMENSIONS	20W: $\Phi 2.95 \times 23.6$ in ($\Phi 75 \times 600$ mm) 36W: $\Phi 2.95 \times 47.2$ in ($\Phi 75 \times 1200$ mm) 45W: $\Phi 2.95 \times 59.1$ in ($\Phi 75 \times 1500$ mm)
OPERATING TEMPERATURE	-4°F ~ +104°F (-20°C ~ +40°C)
WEIGHT	20W: 2.65lbs/1.2kg 36W: 4.85lbs/2.2kg 45W: 5.95lbs/2.7kg
CONSTRUCTION	Polymer Housing, Stainless Steel End-caps
LENS MATERIAL	Polycarbonate or Acrylic
HARDWARE	Marine Grade Stainless Steel
CONNECTION	Single or Series
L70	75,000 Hours
WARRANTY	5 Years

CONTACT OUR TEAM TODAY

1 (833) 4 REDSKY
contact@redskylighting.com
www.redskylighting.com