

Tuff-Tube Series

The Tuff-Tube is perfectly suited for harsh conditions in highly polluted environments where a high level of quality lighting is needed. Rated IP69K with an IK10 shock rating, the Tuff-Tube handles water, dust, humidity, corrosion, and other harsh elements with ease. Designed for use in food processing, agricultural applications, mining, and water treatment plants.

Certification and Ratings

UL1598 Wet Location UL 8750 LED Safety CSA C22.2 No. 250.13-14 NSF Listed (Contact Us)

IP69K IK10 (PC) IK08 (PE)






Dimensions

	Α	В
20W	2.95/75	23.6/600
36W	2.95/75	47.2/1200
45W	2.95/75	59.1/1500
Units: i	n/mm	

Weight

20W 2.65/1.2 36W 4.85/2.2 45W 5.95/2.7 Units: lbs/kgs

Α



AC100-277V 50/60hz
20W 36W 45W
2,700Lm 4,860Lm 6,075Lm
110Lm/W - 140Lm/W
120°
PC or PE Polymer Housing Aluminum Board
>95% @120V
4Kva
-4°F to 104°F (-20°C to 40°C)
Polycarbonate or Acrylic
Stainless Steel Clips and Caps
M20x1.5 SS316 Cable Glands
Ra>80
75,000 Hours
0/1-10V
5 Year Fixture Warranty


*Lens option may affect lumen output


Red Sky Lighting LLC 9370 Pittsburgh Ave Rancho Cucamonga, CA 91730, USA



Order Information Tuff-Tube Series

Example: TFT-20-UNV-5000K-DIFF-PC





Accessories


CHM: Cable Hang Mount


REB: Rebreather Vent (Standard) SCE: Series Connection Endcap***


*PE Lens Material is only available in Diffused lens

***Contact Factory

Photometrics







roduct design and specification is subject to change without notice. See website for most up to date version. 💮 2023 Red Sky Lighting LLC All Rights



^{**}Contact Us for application suitability - Special Order