

CERTIFICATE OF COMPLIANCE

Certificate Number E494317
Report Reference E494317-20170717
Issue Date 2022-OCTOBER-18

Issued to: RED SKY LIGHTING, LLC
410 MAIN STREET RACINE, WI 53403 USA

This certificate confirms that representative samples of LUMINAIRES, NONRECESSED, MARINE
See Addendum Page

Have been evaluated by UL in accordance with the Standard(s) indicated on this Certificate.

Standard(s) for Safety: UL 1598 - Luminaires
UL 1598A - Supplemental Requirements for Luminaires for Installation on Marine Vessels

Additional Information: See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Conformity Assessment Director
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Customer Service at <http://ul.com/about/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number E494317
Report Reference E494317-20170717
Issue Date 2022-OCTOBER-18

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Nonrecessed Marine Luminaires, Outside Type (Salt Water), Models RND-45-100-277-TT[a], RND-65-100-277-TT[a], RND-45-100-277-MARINE-TT[a], RND-65-100-277-MARINE-TT[a], LNR-40-120-277-TT[a], LNR-40-200-480-TT[a], LNR-80-120-277-TT[a], LNR-80-200-277-TT[a], LNR-40-120-277-MARINE-TT[a], LNR-40-200-480-MARINE-TT[a], LNR-80-200-480-MARINE-TT[a], LNR-80-120-277-MARINE-TT[a], BLM [d], LNT-40 [f], LNT-80 [f]

[a] - "TT" may be followed additional characters to indicate CCT, Color, beam angle, lens type, LED type, mount or ID number.

[d] - followed by -21, -40, -50 or -60; may be followed by -120-277 or -347-480; may be followed by

- 27K,3K,4K or -5K; may be followed by -T2, -T3 or -T5; maybe followed by -H1, H2; maybe followed by -CG, -DG or -DP; maybe followed by -PEND, -YOKE, -CEIL, -SN25, -SN90, -WL25 or -WL90; maybe followed by -GRY, -BLK, -WTE or -BRZ.

[f] - Followed by 120-277 or 277-480, followed by -3000K, -4000K or -5000K, followed by -60, -T2 or

-110, followed by H1, followed by CG or DG, followed by -Pend or -Yoke, followed by -Grey,

-Black, -White or -Bronze, may be followed by PS.

Nonrecessed Marine Luminaires, Outside Type (Salt Water), Model BLK followed by -080, -100 or -150; followed by 100-277 (or 120-277) or 200-480; followed by Marine or blank; followed by 3000K, 3500K, 4000K, 4500K, 5000K or 5700K; followed by 25°, 40°, 60°, 80° 100° or 120°; followed by CLR or DF; followed by GREY, BLK, WHT or BRZ; followed by PEND or YOKE; followed by alphanumeric digits for customer designation or blank.



Bruce Mahrenholz, Conformity Assessment Director
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Customer Service at <http://ul.com/about/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number E494317
Report Reference E494317-20170717
Issue Date 2022-OCTOBER-18

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Nonrecessed Marine Luminaires, Outside Type (Salt Water), -

Models BLK; Followed by -80,-100 or -150; Followed by -100-277, -120-277 or -347-480; Followed by -3K, -35K, -4K, -45K, -5K, or -57K; Followed by -25, -40, -60, -80, -100 or -120; Followed by -H1 or -H2; Followed by -CG or -DG; Followed by -GRY,-BLK, -WHT or -BRZ; Followed by -PND or -YKE; Followed by BLANK or -PS. (h)

(h) - 1 – Fixture Series BLK - For all luminaires.

2 – Wattage, 80 - 80W, 100 - 100W, 150 - 150W.

3 – Voltage, 100-277 - 100-240/277 AC, 120-277 - 120-240/277 AC, 347-480 - 347-480V AC.

4 – Color Temperature, 3K - 3000K, 35K - 3500K, 4K - 4000K, 45K - 4500K, 5K - 5000K, 57K - 5700K.

5 – Beam Angle, 25 - 25°, 40 - 40°, 60 - 60°, 80 - 80°, 100 - 100°, 120 - 120°.

6 – Luminaire Series, H1 - For all luminaires, H2 - For all luminaires.

7 – Lens, CG - Clear Glass, DG - Diffuse Glass,

8 – Finish Color, GRY – Grey, BLK – Black, WHT – White, BRZ – Bronze.

9 – Mounting, PND – Pendant, YKE – Yoke.

10 – Luminaire Series, Blank - For all luminaires, PS - For all luminaires

Model - RND; Followed by -40 –45, -60, or –65; Followed by -100-277, -120-277 or -347-480; Followed by -3K, -4K, -5K; Followed by -H2; Followed by -CG, -DG or -DLG; Followed by -GRY, -BLK, -WHT or -BRZ; Followed by -PND, -YKE or -ML. (j)

(j) - 1 – Fixture Series, RND - For all luminaries.

2 – Wattage, 45 - 45W, 65 - 65W, 40 - 40W, 60 - 60W.

3 – Voltage, 100-277 - 100-240/277 AC, 120-277 - 120-240/277 AC, 347-480 - 347-480V AC.

4 – Color Temperature, 3K - 3000K, 4K - 4000K, 5K - 5000K.

5 – Luminaire Series, H2 - For all luminaires.

6 – Lens, CG - Flat Clear Glass 110°, DG - Flat Diffuse Glass 110°, DLG - Diffuse Drop Lens Glass 130°.

7 – Finish Color, GRY – Grey, BLK – Black, WHT – White, BRZ – Bronze.

8 – Mounting, PND – Pendant, YKE – Yoke, ML - Multi



Bruce Mahrenholz, Conformity Assessment Director

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Customer Service at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number E494317
Report Reference E494317-20170717
Issue Date 2022-OCTOBER-18

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Nonrecessed Marine Luminaires, Outside Type (Salt Water) –

Model - LNR; Followed by -40, or -80; Followed by -100-277, -120-277 or -347-480; Followed by -3K, -4K, -5K; Followed by -H2; Followed by -CP or -DP; Followed by -GRY, -BLK, -WHT or -BRZ; Followed by -PND or -YKE (l)

- (l) - 1 – Fixture Series LNR - For all luminaires
- 2 – Wattage, 40 - 40W, 80 - 80W.
- 3 – Voltage, 100-277 - 100-240/277 AC, 120-277 - 120-240/277 AC, 347-480 - 347-480V AC.
- 4 – Color Temperature, 3K - 3000K, 4K - 4000K, 5K - 5000K.
- 5 – Luminaire Series, H2 - For all luminaires.
- 6 – Lens, CP - Clear PC, DP - Diffuse PC.
- 7 – Finish Color, GRY – Grey, BLK – Black, WHT – White, BRZ – Bronze.
- 8 – Mounting, PND – Pendant, YKE - Yoke

Model - LNT; Followed by -40 or -80; Followed by -100-277, -120-277 or -347-480; Followed by -3K, -4K, -5K; Followed by -110, -60 or -T2; Followed by -H1; Followed by -CG or -DG; Followed by -GRY,-BLK, -WHT or -BRZ; Followed by -PND or -YKE; Followed by BLANK or -PS (n)

- (n) - 1 – Fixture Series LNT - For all luminaires.
- 2 – Wattage, 40 - 40W, 80 - 80W.
- 3 – Voltage, 100-277 - 100-277V AC, 120-277 - 120-277V AC, 347-480 - 347-480V AC.
- 4 – Color Temperature, 3K - 3000K, 4K - 4000K, 5K - 5000K.
- 5 – Beam Angle, 110 - 110°, 60 - 60°, T2 - Type II.
- 6 – Luminaire Series, H1 - For all luminaires.
- 7 – Lens, CG - Clear Glass, DG - Diffuse Glass.
- 8 – Finish Color, GRY – Grey, BLK – Black, WHT – White, BRZ – Bronze.
- 9 – Mounting, PND – Pendant, YKE – Yoke.
- 10 – Luminaire Series, Blank - For all luminaires, PS - For all luminaires.



Bruce Mahrenholz, Conformity Assessment Director
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Customer Service at <http://ul.com/about/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number E494317
Report Reference E494317-20170717
Issue Date 2022-OCTOBER-18

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Nonrecessed Marine Luminaires, Outside Type (Salt Water) –

Model - BLM; Followed by -21, -40, -50 or -60; Followed by -120-277 or -347-480; Followed by -27K, -3K, -4K, -5K; Followed by -T2, -T3 or -T5; Followed by -H1 or -H2; Followed by -CG -DG or -DP; Followed by -GRY, -BLK, -WHT or -BRZ; Followed by -PND, -YKE, -CEIL, -SN25, -SN90, -WL25, or -WL90; Followed by BLANK or -PS (p).

(p) - 1 – Fixture Series BLM - For all luminaires.

2 – Wattage, 21 - 21W, 40 - 40W, 50 - 50W, 60 - 60W.

3 – Voltage, 120-277 - 120-277V AC, 347-480 - 347-480V AC.

4 – Color Temperature, 5K - 5000K, 4K - 4000K, 3K - 3000K, 27K - 2700K.

5 – Beam Angle, T2 - Type II, T3 - Type III, T5 - 110°.

6 – Luminaire Series, H1 - For all luminaires, H2 - For all luminaires.

7 – Lens, CG - Clear Glass, DG - Diffuse Glass, DP-Diffused Polycarbonate.

8 – Finish Color, GRY – Grey, BLK – Black, WHT – White, BRZ – Bronze.

9 – Mounting, PND – Pendant, YKE – Yoke, CEIL – Ceiling, SN25 - Stanchion 25°, SN90 - Stanchion 90°, WL25 - Wall 25°, WL90 - Wall 90°.

10 – Luminaire Series, Blank - For all luminaires, PS - For all luminaires.



Bruce Mahrenholz, Conformity Assessment Director

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Customer Service at <http://ul.com/about/locations/>

