

CERTIFICATE OF COMPLIANCE

Certificate Number E494316
Report Reference E494316-20170717
Issue Date 2022-OCTOBER-10

Issued to: RED SKY LIGHTING, LLC
410 MAIN STREET
RACINE, WI 53403 USA

This certificate confirms that representative samples of LIGHT-EMITTING-DIODE SURFACE-MOUNTED LUMINAIRES
See Addendum Page

Have been evaluated by UL in accordance with the Standard(s) indicated on this Certificate.

Standard(s) for Safety: UL 1598 & CSA C22.2 No. 250.0-08 - Luminaires
UL 8750 - Light Emitting Diode (LED) Equipment for Use in Lighting Products
CSA-C22.2 No. 250.13 & CSA C22.2 No. 250.13-17- Light Emitting Diode (LED) Equipment for Lighting Applications

Additional Information: See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Conformity Assessment Director
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Customer Service at <http://ul.com/about/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number E494316
Report Reference E494316-20170717
Issue Date 2022-OCTOBER-10

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Light-emitting-diode Surface-mounted Luminaire, Models RND-45-100-277-TT[a], RND-65-100-277-TT[a], LNR-40-120-277-TT[a], LNR-40-200-480-TT[a], LNR-80-120-277-TT[a], LNR-80-200-480-TT[a], MOD-50-120-277-XX-YYY-TT[a][b], MOD-100-120-277-XX-YYY-TT[a][b], MOD-150-120-277-XX-YYY-TT[a][b], MOD-200-120-277-XX-YYY-TT[a][b], MOD-300-120-277-XX-YYY-TT[a][b]

[a] - TT may be followed additional characters to indicate CCT, Color, beam angle, lens type, LED type, mount or ID number.

[b] - XX represents color temp, YYY represents beam angle, which could be 8°, 25°, 40°, 60°, 90° or 120°.

Light-emitting-diode Surface-mounted Luminaire, Models MOD-400-120-277-XX-YYY-TT[a][b], MOD-150-200-480-XX-YYY-TT[a][b], MOD-200-200-480-XX-YYY-TT[a][b], MOD-300-200-480-XX-YYY-TT[a][b], MOD-400-200-480-XX-YYY-TT[a][b]

LED surface mounted luminaire, Wet location, Models BLK-XXX-120-277-TT[a][c], BLK-XXX-200-480-TT[a][c]

[a] - TT may be followed additional characters to indicate CCT, Color, beam angle, lens type, LED type, mount or ID number.

[b] - XX represents color temp, YYY represents beam angle, which could be 8°, 25°, 40°, 60°, 90° or 120°.

[c] - XXX represents fixture wattage, which could be 80, 100, or 150.

Light-emitting-diode Surface-mounted Luminaire, Models MOD-SL-50-100-277-XX-YY-TT[a][d], MOD-SL-100-100-277-XX-YY-TT[a][d], MOD-SL-150-100-277-XX-YY-TT[a][d], MOD-SL-200-100-277-XX-YY-TT[a][d], MOD-SL-250-100-277-XX-YY-TT[a][d], MOD-SL-300-100-277-XX-YY-TT[a][d], MOD-SL-350-100-277-XX-YY-TT[a][d], MOD-SL-400-100-277-XX-YY-TT[a][d], MOD-SL-400-200-480-XX-YY-TT[a][d]

LED Surface Mounted Luminaire, Models HBH-150-100-277-@@-#[e], HBH-150-347-480-@@-#[e]

[a] - TT may be followed additional characters to indicate CCT, Color, beam angle, lens type, LED type, mount or ID number.

[d] - XX represents color temperature, YY represents beam angle, which could be T2 or 12.

[e] - may be any letter or blank and where # may be 60 or 110 or blank.



Bruce Mahrenholz, Conformity Assessment Director
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Customer Service at <http://ul.com/about/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number E494316
Report Reference E494316-20170717
Issue Date 2022-OCTOBER-10

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

LED Surface Mounted Luminaire, Model BLM (g), LNT-40 (i), LNT-80 (i), MDH-200 (k), MDH-400 (k), MDH-600 (k), MDH-800 (k)

(g) - followed by -21, -40, -50 or -60; may be followed by -120-277 or -347-480; may be followed by -27K,3K,4K or -5K; may be followed by -T2, -T3 or -T5; maybe followed by -H1,H2; maybe followed by -CG, -DG or -DP; maybe followed by -PEND, -YOKE, -CEIL, -SN25, -SN90, -WL25 or -WL90; maybe followed by -GRY, -BLK, -WTE or -BRZ.

(i) - Followed by 120-277 or 277-480, followed by -3000K, -4000K or -5000K, followed by -60, -T2 or -110, followed by H1, followed by CG or DG, followed by -Pend or -Yoke, followed by -Grey, -Black, -White or -Bronze, may be followed by PS.

(k) - Followed by 120-277 or -347-480, followed by -65 or -70, may be followed by -3K or -4K or -5K or -57K, may be followed by -15 or -30 or -60 or -90 or -T3 or -30/120, Other or -120, followed by -CG or -DG or -PC, may be followed by -BL, -GREY or -SPEC.

LED Surface Mounted Luminaire

BLK. Followed by -80,-100 or -150. Followed by -100-277, -120-277 or -347-480. Followed by -3K, -35K, -4K, -45K, -5K, or -57K. Followed by -25, -40, -60, -80, -100 or -120. Followed by -H1 or -H2. Followed by -CG or -DG. Followed by -GRY,-BLK, -WHT or -BRZ. Followed by -PND or -YKE. Followed by BLANK or -PS.

LED Surface Mounted Luminaire

RND. Followed by -40 -45, -60, or -65. Followed by -100-277, -120-277 or -347-480. Followed by -3K, -4K, -5K. Followed by -H2. Followed by -CG, -DG or -DLG. Followed by -GRY,-BLK, -WHT or -BRZ. Followed by -PND, -YKE or -ML.

LED Surface Mounted Luminaire

LNR. Followed by -40, or -80. Followed by -100-277, -120-277 or -347-480. Followed by -3K, -4K, -5K. Followed by -H2. Followed by -CP or -DP. Followed by -GRY,-BLK, -WHT or -BRZ. Followed by -PND or -YKE.

LED Surface Mounted Luminaire

LNT. Followed by -40 or -80. Followed by -100-277, -120-277 or -347-480. Followed by -3K, -4K, -5K. Followed by -110, -60 or -T2. Followed by -H1. Followed by -CG or -DG. Followed by -GRY,-BLK, -WHT or -BRZ. Followed by -PND or -YKE. Followed by BLANK or -PS.

LED Surface Mounted Luminaire

BLM. Followed by -21, -40, -50 or -60. Followed by -120-277 or -347-480. Followed by -27K, -3K, -4K, -5K. Followed by -T2, -T3 or -T5. Followed by -H1 or -H2. Followed by -CG -DG or -DP. Followed by -GRY,-BLK, -WHT or -BRZ. Followed by -PND, -YKE, -CEIL, -SN25, -SN90, -WL25, or -WL90. Followed by BLANK or -PS.



Bruce Mahrenholz, Conformity Assessment Director
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Customer Service at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number E494316
Report Reference E494316-20170717
Issue Date 2022-OCTOBER-10

LED Surface Mounted Luminaire
MDH. Followed by -200, -400, -600 or -800. Followed by -120-277 or -347-480. Followed by -65 or -70. Followed by -3K, -4K, -5K, or -57K. Followed by -15, -30, -60, -90, -T3, -30/120 or -120. Followed by -CG, -DG or -PC. Followed by -GRY,-BLK, -WHT or -BRZ.

LED Surface Mounted Luminaire
Models HBH. Followed by -150. Followed by -120-277 or -347-480. Followed by -4K, -5K, or -57K. Followed by -60 or -110.



Bruce Mahrenholz, Conformity Assessment Director
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Customer Service at <http://ul.com/about/locations/>

