

# CERTIFICATE OF COMPLIANCE

**Certificate Number** E514086  
**Report Reference** E514086-20200603  
**Issue Date** 2022-October-13

**Issued to:** Red Sky Lighting, LLC  
410 Main Street  
Racine, WI 53403 United States

**This certificate confirms that representative samples of** Emergency Lighting and Power Equipment  
See Addendum Page

Have been evaluated by UL in accordance with the Standard(s) indicated on this Certificate.

**Standard(s) for Safety:** UL 924 Emergency Lighting and Power Equipment  
**Additional Information:** See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Conformity Assessment Director  
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Customer Service at <http://ul.com/about/locations/>



# CERTIFICATE OF COMPLIANCE

**Certificate Number** E514086  
**Report Reference** E514086-20200603  
**Issue Date** 2022-October-13

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

LNT-80-120-277-\*\*-@-# (b)

(b) - Where “\*\*\*” may be CG or DG; Where “@” may be 60, T2 or 110°; Where “#” may be optional D or W.

LNT; Followed by -80; Followed by -120-277; Followed by -3K, -4K, -5K; Followed by -110, -60 or -T2; Followed by -H1; Followed by -CG or -DG; Followed by -GRY,-BLK, -WHT or -BRZ; Followed by -PND or -YKE; Followed by -EM.

1 – Fixture Series  
LNT - For all luminaires  
2 – Wattage  
80 - 80W  
3 – Voltage  
120-277 - 120-277V AC  
5 – Beam Angle  
110 - 110°  
60 - 60°  
T2 - Type II  
6 – Luminaire Series  
H1 - For all luminaires  
7 – Lens  
CG - Clear Glass  
DG - Diffuse Glass  
8 – Finish Color  
GRY - Grey  
BLK - Black  
WHT - White  
BRZ - Bronze  
9 – Mounting  
PND - Pendant  
YKE - Yoke  
10 – Battery  
EM – 90 mins



Bruce Mahrenholz, Conformity Assessment Director  
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Customer Service at <http://ul.com/aboutul/locations/>



# CERTIFICATE OF COMPLIANCE

**Certificate Number** E514086  
**Report Reference** E514086-20200603  
**Issue Date** 2022-October-13

LNR; Followed by -40, or -80; Followed by -120-277; Followed by -3K, -4K, -5K or 57K; Followed by -H2; Followed by -CP or -DP; Followed by -GRY,-BLK, -WHT or -BRZ; Followed by -PND or -YKE; Followed by -EM.

1 – Fixture Series

LNR - For all luminaries

2 – Wattage

40 - 40W

80 - 80W

3 – Voltage

120-277 - 120-240/277Vac

4 – Color Temperature

3K - 3000K

4K - 4000K

5K - 5000K

57K - 5700K

5 – Luminaire Series

H2 - For all luminaires

6 – Lens

CP - Clear PC

DP - Diffuse PC

7 – Finish Color

GRY - Grey

BLK - Black

WHT - White

BRZ - Bronze

8 – Mounting

PND - Pendant

YKE - Yoke

9 – Battery

EM – 90 mins



Bruce Mahrenholz, Conformity Assessment Director

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Customer Service at <http://ul.com/aboutul/locations/>

