

Certificate of Compliance

Issued to:

RED SKY LIGHTING, LLC
9370 Pittsburgh Ave, RANCHO CUCAMONGA
CA 91730-5557

This certificate confirms that representative samples of:

LIGHT-EMITTING-DIODE SURFACE-MOUNTED LUMINAIRES

See Addendum Page

Has been evaluated by UL LLC in accordance with Standard(s) for Safety:

[UL 1598 & CSA C22.2 No. 250.0-08 - Luminaires

UL 8750 - Light Emitting Diode (LED) Equipment for Use in Lighting Products

CSA-C22.2 No. 250.13 & CSA C22.2 No. 250.13-17- Light Emitting Diode (LED) Equipment for Lighting Applications]

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.



David Piecuch
UL Mark Certification Program Owner

Certificate Number:

[E494316]

Report Reference:

E494316-20170717

Issue Date:

2025-APRIL-02



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

Certificate of Compliance

Certificate Number: E494316
Report Reference: E494316-20170717
Issue Date: 2025-APRIL-02

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

LED Surface Mounted Luminaire

BLM. Followed by -21, -40, -50 or -60. Followed by -120-277, -120, -208-277 or -347-480. Followed by -27K, -3K, -4K, -5K. Followed by -T2, -T3 or -T5. Followed by -H1,-H2 or -HS. Followed by -CG -DG or -DP. Followed by -GRY,-BLK, -WHT or -BRZ. Followed by -PND, -YKE, -CEIL, -SN25, -SN90, -WL25, -WL90,-PJ01,-PJ02 or -PJ03. Followed by BLANK or -PS.

- 1 – Fixture Series, BLM - For all luminaires,
- 2 – Wattage 21 – 21W,40 - 40W ,50 - 50W, 60 - 60W
- 3 – Voltage 120-277 - 120-277V AC,120 - 120 Vac, 208-277 - 208-277 Vac, 347-480 -347-480V AC
- 4 – Color Temperature 5K - 5000K 4K - 4000K, 3K - 3000K, 27K - 2700K
- 5 – Designates Customer custom. Blank - Blank. HAR- Customer custom
- 6 – Beam Angle T2 - Type II , T3 - Type III , T5 - 110°
- 7 – Luminaire Series : H1 - For all luminaires, H2 - For all luminaires, HS - For all luminaires
- 8 – Lens, CG - Clear Glass , DG - Diffuse Glass, DP-Diffused Polycarbonate,
- 9 – Finish Color GRY – Grey, BLK - Black , WHT - White , BRZ – Bronze,
- 10 – Mounting PND – Pendant, YKE – Yoke, CEIL - Ceiling ,SN25 - Stanchion 25°, SN90 - Stanchion 90° ,WL25 - Wall 25° ,WL90 - Wall 90° ,PJ01 - Pole* & Junction box & U-Bracket,PJ02 - Pole* & Junction box & U-Bracket & Sensor 01(HLPC-120), PJ03 - Pole* & Junction box & U-Bracket & Sensor 02(HLPC-208-277)
- 11 – Paint Spray: Blank - Non Paint Spray , PS - Paint Spray