Certificate of Compliance

Certificate Number:

E494317

Report Reference:

E494317-20170717

Issue Date:

2025-SEPTEMBER-25

Issued to:

Red Sky Lighting LLC 9370 Pittsburgh Ave Rancho Cucamonga, CA 91730 United States

This certificate confirms that representative samples of: LUMINAIRES, NONRECESSED, MARINE See addendum page for models/product

Has been evaluated by UL LLC in accordance with Standard(s) for Safety:

[UL 1598 – Luminaires; UL 1598A - Supplemental Requirements for Luminaires for Installation on Marine Vessels]

Additional Information:

See UL Product iQ[®] at https://iq.ulprospector.com for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.

David Piecuch



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at https://www.ul.com/contact-us.

Page 1 of 2

Certificate of Compliance

Certificate Number: E494317

Report Reference: E494317-20170717 **Issue Date:** 2025-SEPTEMBER-25

UL Mark Certification Program Owner

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Models:

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Nonrecessed Marine Luminaires, Outside Type (Salt Water), -

Models RDX; followed by -5L, -7L, -9L, -12L, -18L, -22L or -28L; followed by -100-277; followed by -65K, -57K, -5K, -4K, -3K or -27K; followed by -Blank, -HAR or -YYY; followed by -30, -60, -T5, -T1 or -T3; followed by -H2 or -HS; followed by -CG, -DG, -DLG, -CP or -DP; followed by -GRY, -BLK, -WHT or -BRZ; followed by -PDCG or -YKE; followed by -EM01 or -EM02; followed by -Blank, -BAA, -BABA or -XXXX.

Models RDX; followed by -5L, -7L, -9L, -12L, -18L, -22L or -28L; followed by -100-277, -120 or -208-277; followed by -65K, -57K, -5K, -4K, -3K or -27K; followed by -Blank, -HAR or -YYY; followed by -30, -60, -T5, -T1 or -T3; followed by -H3 or -HS; followed by -CG, -DG, -DLG, -CP or -DP; followed by -GRY, -BLK, -WHT or -BRZ; followed by -JB01, -JB02-P, -JB03-P, -JB04, -JB05-P or -JB06-P; followed by -EM01 or -EM02; followed by -Blank, -BAA, -BABA or -XXXX.

