

Certificate of Compliance

Certificate Number:

[E494317]

Report Reference:

E494317-20231219

Issue Date:

2024-02-20

Issued to:

Red Sky Lighting LLC

9370 Pittsburgh Ave, RANCHO CUCAMONGA, CA 91730-5557

This certificate confirms that representative samples of:
LUMINAIRES, NONRECESSED, MARINE
See addendum page for models

Has been evaluated by UL LLC in accordance with Standard(s) for
Safety:

**[UL 1598 - Luminaires
UL 1598A - Supplemental Requirements for Luminaires for
Installation on Marine Vessels]**

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional
information.

This Certificate of Compliance indicates that representative samples of
the product described in the certification report have met the
requirements for UL certification. It does not provide authorization to
apply the UL Mark. Only the Authorization Page that references the
Follow-Up Services Procedure for ongoing surveillance provides
authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as
being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



David Piecuch
UL Mark Certification Program Owner



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized
licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

Certificate of Compliance

Certificate Number: E494317
Report Reference: E494317-20170717
Issue Date: 2024-02-20

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

BLK2. Followed by -80, -100, -120 or -150. Followed by -100-277, -347-480. Followed by -27K, -3K, -4K, -5K, -57K, -65K. Followed by -25, -60 or -120. Followed by -H1, -H2 or -HS. Followed by -CG or -DG. Followed by -GRY, -BLK, -WHT or -BRZ. Followed by -PND or -YKE. Followed by BLANK or -PS.

1 –Series Type BLK 2– For all luminaires.

2 – Wattage 80 – 80 W, 100 – 100 W, 120 – 120 W, 150 – 150 W.

3 –Voltage 100-277- 100~277Vac,
347-480 - 347~480Vac.

4 –LED Color temperature (CCT).

27K – 2700K, 3K – 3000K, 4K – 4000K,

5K – 5000K, 57K – 5700K, 65K– 6500K,

5- Optic Beam Angle. 25 - 25°, 60 - 60°,
120 - 120°(non-optic).

6 – Basic Model Series. H1- For all luminaires. H2- For all luminaires. HS –For UL1598/A.

7 - Lens Type. CG- Clear Glass. DG- Diffused Glass.

8 –Color of Finish. GRY - Grey, BLK - Black, WHT - White, BRZ - Bronze.

9 –Mounting. PND - Pendant , YKE - Yoke.

10 - Paint Spray. Blank – Non Paint Spray Use, PS – Paint Spray Use.