

# Certificate of Compliance

**Certificate Number:**

[E494317]

**Report Reference:**

E494317-20170717

**Issue Date:**

2025-MARCH-07

Issued to:

**Red Sky Lighting LLC**

**9370 Pittsburgh Ave, RANCHO CUCAMONGA, CA 91730-5557**

This certificate confirms that representative samples of:  
**LUMINAIRES, NONRECESSED, MARINE**  
**See addendum page for models**

Has been evaluated by UL LLC in accordance with Standard(s) for  
Safety:

**[UL 1598 - Luminaires  
UL 1598A - Supplemental Requirements for Luminaires for  
Installation on Marine Vessels]**

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional  
information.

This Certificate of Compliance indicates that representative samples of  
the product described in the certification report have met the  
requirements for UL certification. It does not provide authorization to  
apply the UL Mark. Only the Authorization Page that references the  
Follow-Up Services Procedure for ongoing surveillance provides  
authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as  
being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



David Piecuch  
UL Mark Certification Program Owner



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

# Certificate of Compliance

**Certificate Number:** E494317  
**Report Reference:** E494317-20170717  
**Issue Date:** 2025-MARCH-07

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

BLK2. Followed by -80, -100, -120 or -150. Followed by -100-277, -347-480. Followed by -27K, -3K, -4K, -5K, -57K, -65K. Followed by BLANK or -HAR, Followed by -25, -60 or -120. Followed by -H1, -H2 or -HS. Followed by -CG or -DG. Followed by -GRY, -BLK, -WHT or -BRZ. Followed by -PND or -YKE. Followed by BLANK or -PS.

1 –Series Type, BLK2 – For all luminaires.

2 – Wattage, 80 – 80 W, 100 – 100 W, 120 – 120 W, 150 – 150 W.

3 –Voltage 100-277- 100~277Vac, 347-480 - 347~480Vac.

4 –LED Color temperature (CCT). 27K – 2700K, 3K – 3000K, 4K – 4000K, 5K – 5000K, 57K – 5700K, 65K– 6500K.

5 – Designates Customer custom. Blank - Blank. HAR – custom.

6- Optic Beam Angle. 25 - 25°, 60 - 60°, 120 - 120°(non-optic).

7 – Basic Model Series. H1- For all luminaires, H2- For all luminaires, HS –For UL1598/A.

8 - Lens Type. CG- Clear Glass. DG- Diffused Glass.

9 –Color of Finish. GRY - Grey, BLK - Black, WHT - White, BRZ - Bronze.

10 –Mounting. PND – Pendant, YKE - Yoke.

11 - Paint Spray. Blank – Non Paint Spray Use, PS – Paint Spray Use.