

# CERTIFICATE OF COMPLIANCE

**Certificate Number** E514086  
**Report Reference** E514086-20200603  
**Issue Date** 2024-FEBRUARY-20

**Issued to:** Red Sky Lighting LLC  
9370 Pittsburgh Ave, RANCHO CUCAMONGA, CA 91730-5557

**This certificate confirms that representative samples of** Emergency Lighting and Power Equipment  
See Addendum Page


Have been evaluated by UL in accordance with the Standard(s) indicated on this Certificate.

**Standard(s) for Safety:** UL 924 Emergency Lighting and Power Equipment  
**Additional Information:** See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Conformity Assessment Director

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Customer Service at <http://ul.com/aboutul/locations/>



# CERTIFICATE OF COMPLIANCE

**Certificate Number** E514086  
**Report Reference** E514086-20200603  
**Issue Date** 2024-FEBRUARY-20

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

LNT-80-120-277-\*\*-@-# (b)

(b) - Where “\*\*” may be CG or DG; Where “@” may be 60, T2 or 110°; Where “#” may be optional D or W.

LNT; Followed by -80; Followed by -120-277; Followed by -3K, -4K, -5K; Followed by -110, -60 or -T2; Followed by -H1; Followed by -CG or -DG; Followed by -GRY, -BLK, -WHT or -BRZ; Followed by -PND or -YKE; Followed by -EM.

1 – Fixture Series

LNT - For all luminaires

2 – Wattage

80 - 80W

3 – Voltage

120-277 - 120-277V AC

5 – Beam Angle

110 - 110°

60 - 60°

T2 - Type II

6 – Luminaire Series

H1 - For all luminaires

7 – Lens

CG - Clear Glass

DG - Diffuse Glass

8 – Finish Color

GRY - Grey

BLK - Black

WHT - White

BRZ - Bronze

9 – Mounting

PND - Pendant

YKE - Yoke

10 – Battery

EM – 90 mins



Bruce Mahrenholz, Conformity Assessment Director

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Customer Service at <http://ul.com/aboutul/locations/>



# CERTIFICATE OF COMPLIANCE

Certificate Number E514086  
Report Reference E514086-20200603  
Issue Date 2024-FEBRUARY-20

LNR; Followed by -40, or -80; Followed by -120-277; Followed by -3K, -4K, -5K; Followed by -H2;  
Followed by -CP or -DP; Followed by -GRY,-BLK, -WHT or -BRZ; Followed by -PND or -YKE; Followed  
by -EM.

1 – Fixture Series

LNR - For all luminaries

2 – Wattage

40 - 40W

80 - 80W

3 – Voltage

120-277 - 120-240/277Vac

4 – Color Temperature

3K - 3000K

4K - 4000K

5K - 5000K

57K - 5700K

5 – Luminaire Series

H2 - For all luminaires

6 – Lens

CP - Clear PC

DP - Diffuse PC

7 – Finish Color

GRY - Grey

BLK - Black

WHT - White

BRZ - Bronze

8 – Mounting

PND - Pendant

YKE - Yoke

9 – Battery

EM – 90 mins



Bruce Mahrenholz, Conformity Assessment Director

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please  
contact UL Customer Service at <http://ul.com/aboutul/locations/>

