

Certificate of Compliance

Certificate Number:

[E494315]

Report Reference:

E494315-20170712

Issue Date:

2024-02-20

Issued to:

Red Sky Lighting LLC

**9370 Pittsburgh Ave, RANCHO CUCAMONGA, CA
91730-5557**

This certificate confirms that representative samples of:

**LUMINAIRES FOR USE IN HAZARDOUS
LOCATIONS**

See addendum page for models

Has been evaluated by UL LLC in accordance with Standard(s) for
Safety:

**[See addendum page for Standard No. &
Title]**

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional
information.

This Certificate of Compliance indicates that representative samples of
the product described in the certification report have met the
requirements for UL certification. It does not provide authorization to
apply the UL Mark. Only the Authorization Page that references the
Follow-Up Services Procedure for ongoing surveillance provides
authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as
being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



David Piecuch
UL Mark Certification Program Owner



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

Certificate of Compliance

Certificate Number: E494315
Report Reference: E494315-20170712
Issue Date: 2024-02-20

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Standards for Safety:

UL 844 Luminaires for Use in Hazardous (Classified) Locations
CSA C22.2 No. 137-M1981 Electric Luminaires for Use in Hazardous Locations
UL 8750 Light Emitting Diode (LED) Equipment for use in Lighting Product
UL 1598 and CSA C22.2 NO. 250.0 Luminaires
CSA C22.2 NO. 250.13 Light Emitting Diode (LED) Equipment for Lighting Applications
CSA C22.2 No. 30-M1986, Explosion-proof Enclosures for Use in Class I Hazardous Locations
CSA C22.2 No. 25-1966, Enclosures for Use in Class II Groups E, F, and G Hazardous Locations
CSA C22.2 No. 137 - Electric Luminaires for Use in Hazardous Locations

LNR2-30-100-277

Followed by -27K, -3K, -4K, -5K, -57K, -65K, -RD, -GN, -BU or -AM. Followed by H2. Followed by -CP or -DP. Followed by -GRY, -BLK, -WHT or -BRZ. Followed by -PND or -YKE.

LNR2-30-347-480

Followed by -27K, -3K, -4K, -5K, -57K, -65K, -RD, -GN, -BU or -AM. Followed by H2. Followed by -CP or -DP. Followed by -GRY, -BLK, -WHT or -BRZ. Followed by -PND or -YKE

LNR2-40-100-277

Followed by -27K, -3K, -4K, -5K, -57K, -65K, -RD, -GN, -BU or -AM. Followed by H2. Followed by -CP or -DP. Followed by -GRY, -BLK, -WHT or -BRZ. Followed by -PND or -YKE.

LNR2-40-347-480

Followed by -27K, -3K, -4K, -5K, -57K, -65K, -RD, -GN, -BU or -AM. Followed by H2. Followed by -CP or -DP. Followed by -GRY, -BLK, -WHT or -BRZ. Followed by -PND or -YKE.

LNR2-60-100-277

Followed by -27K, -3K, -4K, -5K, -57K, -65K, -RD, -GN, -BU or -AM. Followed by H2. Followed by -CP or -DP. Followed by -GRY, -BLK, -WHT or -BRZ. Followed by -PND or -YKE.

LNR2-60-347-480

Followed by -27K, -3K, -4K, -5K, -57K, -65K, -RD, -GN, -BU or -AM. Followed by H2. Followed by -CP or -DP. Followed by -GRY, -BLK, -WHT or -BRZ. Followed by -PND or -YKE.

LNR2-80-100-277

Followed by -27K, -3K, -4K, -5K, -57K, -65K, -RD, -GN, -BU or -AM. Followed by H2. Followed by -CP or -DP. Followed by -GRY, -BLK, -WHT or -BRZ. Followed by -PND or -YKE.

LNR2-80-347-480

Followed by -27K, -3K, -4K, -5K, -57K, -65K, -RD, -GN, -BU or -AM. Followed by H2. Followed by -CP or -DP. Followed by -GRY, -BLK, -WHT or -BRZ. Followed by -PND or -YKE