

Certificate of Compliance

Certificate Number:

[E494316]

Report Reference:

E494316-20240109

Issue Date:

2024-02-20

Issued to:

RED SKY LIGHTING, LLC
9370 Pittsburgh Ave, RANCHO
CUCAMONGA CA 91730-5557

This certificate confirms that representative samples of:

LIGHT-EMITTING-DIODE SURFACE-MOUNTED LUMINAIRES

See Addendum Page

Has been evaluated by UL LLC in accordance with Standard(s) for Safety:

[CSA C22.2 No. 250.0 Luminaires & UL 1598 Luminaires]

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.



David Piecuch
UL Mark Certification Program Owner

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.



Certificate of Compliance

Certificate Number: E494316
Report Reference: E494316-20240109
Issue Date: 2024-02-20

LED Surface Mounted Luminaire,

LNT2-30-120-277 followed by -27K, -3K, -4K, -5K, -57K, -65K. followed by -110, -60 or -T2.
followed by -H1 or HS. followed by -CG or -DG. followed by -GRY, -BLK, -WHT or -BRZ.
followed by -PND or -YKE. followed by BLANK or -PS.

LNT2-30-347-480 followed by -27K, -3K, -4K, -5K, -57K, -65K. followed by -110, -60 or -T2.
followed by -H1 or HS. followed by -CG or -DG. followed by -GRY, -BLK, -WHT or -BRZ.
followed by -PND or -YKE. followed by BLANK or -PS.

LNT2-40-120-277 followed by -27K, -3K, -4K, -5K, -57K, -65K. followed by -110, -60 or -T2.
followed by -H1 or HS. followed by -CG or -DG. followed by -GRY, -BLK, -WHT or -BRZ.
followed by -PND or -YKE. followed by BLANK or -PS.

LNT2-40-347-480 followed by -27K, -3K, -4K, -5K, -57K, -65K. followed by -110, -60 or -T2.
followed by -H1 or HS. followed by -CG or -DG. followed by -GRY, -BLK, -WHT or -BRZ.
followed by -PND or -YKE. followed by BLANK or -PS.

LNT2-60-120-277 followed by -27K, -3K, -4K, -5K, -57K, -65K. followed by -110, -60 or -T2.
followed by -H1 or HS. followed by -CG or -DG. followed by -GRY, -BLK, -WHT or -BRZ.
followed by -PND or -YKE. followed by BLANK or -PS.

LNT2-60-347-480 followed by -27K, -3K, -4K, -5K, -57K, -65K. followed by -110, -60 or -T2.
followed by -H1 or HS. followed by -CG or -DG. followed by -GRY, -BLK, -WHT or -BRZ.
followed by -PND or -YKE. followed by BLANK or -PS.

LNT2-80-120-277 followed by -27K, -3K, -4K, -5K, -57K, -65K. followed by -110, -60 or -T2.
followed by -H1 or HS. followed by -CG or -DG. followed by -GRY, -BLK, -WHT or -BRZ.
followed by -PND or -YKE. followed by BLANK or -PS.

LNT2-80-347-480 followed by -27K, -3K, -4K, -5K, -57K, -65K. followed by -110, -60 or -T2.
followed by -H1 or HS. followed by -CG or -DG. followed by -GRY, -BLK, -WHT or -BRZ.
followed by -PND or -YKE. followed by BLANK or -PS.