

# Certificate of Compliance

**Certificate Number:**

[E494315]

**Report Reference:**

E494315-20240111

**Issue Date:**

2024-02-20

Issued to:

**Red Sky Lighting LLC**

**9370 Pittsburgh Ave, RANCHO CUCAMONGA, CA  
91730-5557**

This certificate confirms that representative samples of:

## **LUMINAIRES FOR USE IN HAZARDOUS LOCATIONS**

**See addendum page for models**

Has been evaluated by UL LLC in accordance with Standard(s) for Safety:

**[See addendum page for Standard No. & Title]**

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



David Piecuch  
UL Mark Certification Program Owner



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

# Certificate of Compliance

**Certificate Number:** E494315  
**Report Reference:** E494315-20240111  
**Issue Date:** 2024-02-20

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Standard :

Standard No. UL 844 - Luminaires for Use in Hazardous (Classified) Locations

Standard No. CSA C22.2 No. 137 - Electric Luminaires for Use in Hazardous Locations

Class I, Division 1, Groups C and D; Class I, Division 2, Groups A, B, C and D, Luminaires :  
LNT2-30-120-277

Followed by -27K, -3K, -4K, -5K,-57K,-65K. Followed by -110, -60 or -T2. Followed by -H1. Followed by -CG or -DG. Followed by -GRY, -BLK, -WHT or -BRZ. Followed by -PND or -YKE. Followed by BLANK or -PS.

LNT2-30-347-480

Followed by -27K, -3K, -4K, -5K,-57K,-65K. Followed by -110, -60 or -T2. Followed by -H1. Followed by -CG or -DG. Followed by -GRY, -BLK, -WHT or -BRZ. Followed by -PND or -YKE. Followed by BLANK or -PS.

LNT2-40-120-277

Followed by -27K, -3K, -4K, -5K,-57K,-65K. Followed by -110, -60 or -T2. Followed by -H1. Followed by -CG or -DG. Followed by -GRY, -BLK, -WHT or -BRZ. Followed by -PND or -YKE. Followed by BLANK or -PS.

LNT2-40-347-480

Followed by -27K, -3K, -4K, -5K,-57K,-65K. Followed by -110, -60 or -T2. Followed by -H1. Followed by -CG or -DG. Followed by -GRY, -BLK, -WHT or -BRZ. Followed by -PND or -YKE. Followed by BLANK or -PS.

LNT2-60-120-277

Followed by -27K, -3K, -4K, -5K,-57K,-65K. Followed by -110, -60 or -T2. Followed by -H1. Followed by -CG or -DG. Followed by -GRY, -BLK, -WHT or -BRZ. Followed by -PND or -YKE. Followed by BLANK or -PS.

LNT2-60-347-480

Followed by -27K, -3K, -4K, -5K,-57K,-65K. Followed by -110, -60 or -T2. Followed by -H1. Followed by -CG or -DG. Followed by -GRY, -BLK, -WHT or -BRZ. Followed by -PND or -YKE. Followed by BLANK or -PS.

LNT2-80-120-277

Followed by -27K, -3K, -4K, -5K,-57K,-65K. Followed by -110, -60 or -T2. Followed by -H1. Followed by -CG or -DG. Followed by -GRY, -BLK, -WHT or -BRZ. Followed by -PND or -YKE. Followed by BLANK or -PS.

LNT2-80-347-480

Followed by -27K, -3K, -4K, -5K,-57K,-65K. Followed by -110, -60 or -T2. Followed by -H1. Followed by -CG or -DG. Followed by -GRY, -BLK, -WHT or -BRZ. Followed by -PND or -YKE. Followed by BLANK or -PS.

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

