

Certificate of Compliance

Certificate Number:

E514086

Report Reference:

E514086-20200603

Issue Date:

2025-SEPTEMBER-25

Issued to:

Red Sky Lighting LLC

9370 Pittsburgh Ave

Rancho Cucamonga, CA 91730 United States

This certificate confirms that representative samples of:
EMERGENCY LIGHTING AND POWER EQUIPMENT
See addendum page for models/product

Has been evaluated by UL LLC in accordance with Standard(s) for Safety:

[UL 924 - Emergency Lighting and Power Equipment]

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



David Piecuch

UL Mark Certification Program Owner

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.



Certificate of Compliance

Certificate Number: E514086
Report Reference: E514086-20200603
Issue Date: 2025-SEPTEMBER-25

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Models:

LNR; Followed by -40, or -80; Followed by -120-277; Followed by -3K, -4K, -5K; Followed by -H2 or -HS; Followed by -CP or -DP; Followed by -GRY, -BLK, -WHT or -BRZ; Followed by -PND or -YKE; Followed by -EM.

1 – Fixture Series
LNR - For all luminaries
2 – Wattage
40 - 40W
80 - 80W
3 – Voltage
120-277 - 120-240/277Vac
4 – Color Temperature
3K - 3000K
4K - 4000K
5K - 5000K
57K - 5700K
5 – Luminaire Series
H2 - For all luminaires, HS - UL924
6 – Lens
CP - Clear PC
DP - Diffuse PC
7 – Finish Color
GRY - Grey
BLK - Black
WHT - White
BRZ - Bronze
8 – Mounting
PND - Pendant
YKE - Yoke
9 – Battery
EM – 90 mins